

EU TYPE-EXAMINATION CERTIFICATE

according to Article 19 (c) of Regulation (EU) 2016/425 of the European Parliament and of the Council

No. 1019-193/Q/2025

Name of product:	Full body harness of A5, type HH-A9592
PPE category:	III.
Manufacturer:	Zhejiang Bingfeng Outdoor Product Co., LTD. No. 200 Guangfu Xijie 322100 DONGYANG China
Applied standards and/or technical specification:	ČSN EN 361:2003 (identical to EN 361:2002) ČSN EN 358:2019 (identical to EN 358:2018) ČSN EN 813:2024 (identical to EN 813:2024) ČSN EN 365:2005 (identical to EN 365:2004)
Base for issue of certificate:	Evaluation Report No. 1019-022485/2025, 1 st edition (integral part of this certificate)
Conditions of validity:	Certificate shall only be used in conjunction with one of the conformity assessment procedures referred to Article 19 (c) point (i) or (ii) of Regulation (EU) 2016/425 of the European Parliament and of the Council.
Validity of certificate:	May 23, 2025 – May 22, 2030
Edition:	1 st

VVUU, a.s. hereby certifies that the sample of the product mentioned above meets all the relevant essential health and safety requirements of Annex II of the Regulation (EU) 2016/425 of the European Parliament and of the Council.

May 23, 2025

.....
Date of issue




Tomáš Dorazil

.....
Deputy Director NB 1019

Description of product

Composition of product:	The shoulder straps with the support, waist belt with the support, leg loops with the support	
Width of primary straps:	Webbing (44 mm) Polyester (PES)	
Buckles:	BFP1402 (adjustment buckle)	1 pc on the shoulder straps 1 pc on the back strap 2 pcs on the waist belt 2 pcs on the back straps for loops
	BFP1532 (adjustment buckle)	1 pc on the waist belt (back side)
	BFP2020 (quick release - connection)	1 pc on the shoulder strap
	BFP2020P (quick release - connection)	2 pcs on the leg loops
	H-KKH12 O-ring (connection buckle)	1 pc on the middle front connection strap
Connection item:	Chest rope clamp HH-XS07	1 pc on the middle front connection strap
Threads	PA, in contracting colour to straps	
Attachment points:	1 front point (D-ring) and 1 back point (D-ring) for fall arrest (EN361) 2 lateral belt points (D-rings), 1 lower front belt point (D-ring), 1 back belt point (webbing loop) for work positioning (EN 358) 1 lower front belt point (D-ring) for work positioning (EN 813)	
Max. loading:	140 kg	
Trademark	XINDA	

Picture of product

